Top Coat

UV resistant acrylic aqueous paint

Royal Paints

Generic Description : High built acrylic resin emulsion paint

Uses : As a high quality finishing coat for interior and exterior, new and painted surfaces and also suitable as a top coat for multi layer coatings

Area of Application :Suitable primed surfaces of concrete, plaster, masonary, brickwork, PC panel, GRC panel, hard and soft boards etc,.

Characteristics :Highly resistant again mould and fungus growth

Its water based paint / safe and easy application

Excelent water and alkali resistance

Forms a tough film that is washable

Excellent wethering durability and colour resistant

Good adhesion onto previously painted surface hence suitable for repainting purpose

Good UV resistance

Quick drying.

Colour Availability : clear transparent / A wide range of colours.

TECHNICAL DATA

Finish		Matt / semi-gloss
Specific Gravity		1.23+0.05
Drying time (at 30 C)	Surface dry	30 minutes
	Hard dry	1 1/2 hours
Shelf Life		Up to 6 months if stored in tightly sealed container
Film Thickness	Dry film	30 microns
Solid Content		51+3%
Viscosity		65+10 ps/30 C

THERMOSTONE

APPLICATION DATA

Surface application	Surface shall be dry and free from dirt, dust, oil, grease and foreign matters. Surface unevenness, cracks, etc. shall be made good with our cementitous filler
No of Components	One
No of Coats	One/Two
Coverage coat	0.30-0.40kg/m2
Dilution	0-15% by weight with water
Over coating interval	2 hours
Method of Application	By Spray, Roller or Brush

PACKING STYLE

Top Coat	20 kg/can
Concrete effect stucco	20 kg/can
Royal Sealer	20 kg/can

MATERIAL HANDLING

Store material in a cool, well-ventilated and dry place, away from direct sunlight.

Ensure adequate ventilation during application

Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment

If swallowed, seek medical advice immediately. Do not induce vomitting

Keep away from heat source

For more information, please fell free to contact the following office

THERMO STONE FZE,
PO Box:41838,
Sharjah Hamriyah Free Zone,
Tel : ++971 65260646,
Fax : ++971 65260647,
E mail : info@thermostones.com

Note

The above technical information / values are given to the best of our knowledge based on labaratory tests and practical experience. However due to different applications, site condtions and constraints which are beyond our control, we are not liable for any circumstances. due to or relating to the applicstion or usage of our product. We serve the right to alter or modify the product and any data given without any prior notice, therefore it is best to contact us should you have any doubts or enquiries

THERMOSTONE