

# Green Coat

## Gloss Acrylic Aqueous Paint



Royal Paints

<b>Generic Description</b>	:Pure Acrylic Resin gloss emulsion paint
<b>Uses</b>	:As a high quality finishing coat for interior and exterior, new and painted surfaces and also suitable as a top coat for multi layer coatings
<b>Area of Application</b>	:Suitable primed surfaces of concrete, plaster, masonry, brickwork, PC panel, GRC panel, hard and soft boards etc.,
<b>Characteristics</b>	:Highly resistant against mould and fungus growth Its water based nature ensure safe and easy application Excellent water and alkali resistance Forms a tough film that is washable Excellent weathering durability and colour resistant Good adhesion onto previously painted surface hence suitable for repainting purpose Good gloss retention Quick drying.
<b>Colour Availability</b>	:A wide range of colours.

### TECHNICAL DATA

<b>Finish</b>		Gloss & Semi Gloss
<b>Specific Gravity</b>		1.23+0.05
<b>Drying time (at 30 C)</b>	Surface dry	30 minutes
	Hard dry	1 1/2 hours
<b>Shelf Life</b>		Up to 6 months if stored in tightly sealed container
<b>Film Thickness</b>	Dry film	40-55 microns
<b>Solid Content</b>		51+3%
<b>Viscosity</b>		65+10 ps/30 C

## **APPLICATION DATA**

<b>Surface application</b>	Surface shall be dry and free from dirt, dust, oil, grease and foreign matters. Surface unevenness, cracks, etc. shall be made good with our cementitious filler
<b>No of Components</b>	One
<b>No of Coats</b>	Two
<b>Coverage</b>	0.30-0.40kg/m <sup>2</sup>
<b>Dilution</b>	0-15% by weight with water
<b>Over coating interval</b>	2 hours
<b>Method of Application</b>	By Spray, Roller or Brush

## **PACKING STYLE**

Green Coat	20 kg/can
Texture No 285	20 kg/can
Royal Sealer	20 kg/can

## **MATERIAL HANDLING**

Store material in a cool, well-ventilated and dry place, away from direct sunlight.

Ensure adequate ventilation during application

Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment

If swallowed, seek medical advice immediately. Do not induce vomiting

Keep away from heat source

## **WARRANTY PERIOD ; 5 years from the date of completion**

For more information, please feel free to contact the following office

THERMO STONE FZE,  
PO Box:41838,  
Sharjah Hamriyah Free Zone,  
Tel : ++971 65260646,  
E mail : info@thermostones.com

### **Note**

The above technical information / values are given to the best of our knowledge based in our in-house laboratory tests carried out as per the International standard and our practical experience. However due to different applications, site conditions, surface strength and constraints which are beyond our control, we are not liable for any circumstances, due to or relating to the application or usage of our product. We serve the right to alter or modify any data given without any prior notice, therefore it is best to contact us should you have any doubts or enquiries